

olivetti



d-COPIA 403MF^{en} and 404MF^{en}

MULTIFUNCTIONAL MONOCHROME SYSTEMS

The d-Copia 403MFen and d-Copia 404MFen monochrome A4 multifunctional systems deliver a scan speed of 35 ipm and print and copy at 40 ppm, making them the perfect choice for groups with **heavy workloads**.

Both systems provide maximum **flexibility** for document production: they handle paper weights of up to 220 g/m² and up to five paper feeds, for a total of 2,100 cut sheets.

Full security is guaranteed for shared use of the d-Copia 403MFen and 404MFen, thanks to their advanced network functions including IPsec, SSL and LDAP, and **authentication** with passwords or company badges to restrict access to functions.

The high-capacity toner and 300,000 page drum combine **high quality and savings** to keep running costs and environmental impact to a minimum.

STANDARD PRINT, COPY, COLOUR SCAN AND FAX (404MF^{en} ONLY) FUNCTIONS

STANDARD DUPLEX AND RADF

FIRST COPY OUT IN LESS THAN 7 SECONDS

PRINT RESOLUTION 1200 X 1200 dpi

POWERFUL PROCESSOR, 667 MHz

DOCUMENT TRANSMISSION VIA SCAN-TO-EMAIL/FTP/SMB/USB

REDUCED CONSUMPTION THANKS TO WHITE-LIGHT LEDS FOR SCAN AND COPY JOBS

MINIMAL RUNNING COSTS

TECHNICAL CHARACTERISTICS

GENERAL	Type desktop/console	Desktop	Power Consumption	Copy/print: 677W Stand-by: 96W (403M ^{Fen}) / 98W (404M ^{Fen}) Energy saving mode: 6.9W (403M ^{Fen}) / 10.6W (404M ^{Fen})
	Technology	Mono-component indirect laser		
	Operator panel	5-line LCD Display		
	RAM Memory	256 MB standard (max 768 MB)		
	Interfaces	USB 2.0 (Hi-Speed), USB Host, Fast Ethernet 10/100Base-TX slot for optional CompactFlash card	Noise Level (ISO 7779/ISO 9296)	Copy/print: 55 dB(A) Stand-by: 30 dB(A)
	Warm-up time	Approx. 22 seconds from power on	Dimensions (WxDxH)	494 x 497,1 x 545,1 mm
	Accounting	20 departmental codes	Weight	Approx. 25,5 kg (403M ^{Fen}) Approx. 25,8 kg (404M ^{Fen})
	Monthly duty cycle	200,000 pages max		
Power requirements	220-240 VAC, 50/60 Hz	Consumables (ISO/IEC 19752)	First equipment toner: up to 7,500 pages Toner: up to 15,000 pages	
PRINTER	Speed	Up to 40 ppm	Operating systems	All current Windows operating systems Macintosh OS X 10.4 or later, Unix, Linux
	Time to first print	9,5 seconds		
	Processor speed	PowerPC 440 / 667 MHz	Fonts	93 scalable (PCL6, KPDL3) + 8 (Windows Vista), 1 bitmap, 101 KPDL3, 1 bitmap, 45 types of monodimensional barcodes and 1 two-dimensional (PDF417)
	Resolution	1200 x 1200 dpi		
Languages	PCL 6 (5c/XL), KPDL 3 (PostScript 3 compatible), Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630, PDF Direct Print, XPS Direct Print (with additional memory)	Functions	Encrypted PDF direct print, IPP print, e-mail print, WSD print, secure print via SSL/IPsec/SNMPv3, private print (with additional memory)	
SCANNER	Document input	RADF, flatbed	File formats	TIFF, PDF, JPEG, XPS
	Speed	Up to 35 ipm (600 dpi, A4, B&W), 25 ipm (300 dpi, A4, colour)	Scan modes	TWAIN (USB), WSD (WIA) scan (USB), Scan-to-Email/FTP/SMB/USB Host
	Resolution	600, 400, 300, 200 dpi (256 grayscale)		
	Max scan format	Max A4, Legal	Functions	Colour scan, address-book, LDAP support, encrypted data transfer, multiple simultaneous send (e-mail, fax, SMB/FTP folder, print)
COPIER	Speed	Up to 40 cpm	Multicopy	1-999
	First copy time	7 seconds	Exposure modes	Manual/automatic, 7 levels
	Resolution	600 x 600 dpi	Functions	Duplex copy, layout mode (2-in1, 4-in1), density adjustment, electronic sort, ID copy, auto cassette change, scan-once-copy-many, split copy, job reserve, priority print, program/ recall job, continuous scan
	Image adjustment	Text, photo+text, photo		
Zoom	25% - 400% (1% step)			
FAX (only d-Copia 404M ^{Fen})	Compatibility	ITU-T G3	Memory	256 pages or more
	Speed	33.6 Kbps	One-touch dial	22 destinations
	Transmission time	Less than 3 seconds/page	Address book	100 entries
	Compression	MH, MR, MMR, JBIG		
	Scan density	Normal: 8 points/mm x 3,85 lines/mm Fine: 8 points/mm x 7,7 lines/mm Superfine: 8 points/mm x 15,4 lines/mm Ultrafine: 16 points/mm x 15,4 lines/mm	Functions	Network fax, duplex/encrypted/polling and broadcast transmission/reception
PAPER HANDLING	Paper cassette	500 sheets Paper formats: A6-A4, custom (105 x 148 to 216 x 356 mm) Paper weight: 60-120 g/m ²	Duplex	Standard Paper formats: A5-A4, custom (140 x 210 to 216 x 356 mm) Paper weight: 60-120 g/m ²
	Multi-purpose tray	100 sheets Paper formats: A6-A4, custom (70 x 148 to 216 x 356 mm) Paper weight: 60-220 g/m ²		
	Output paper capacity	500 sheets face down, with full tray sensor	Automatic document feeder	50-sheet RADF Standard Paper formats: A5-A4, custom (140 x 210 to 216 x 356 mm) Paper weight: 50-120 g/m ² simplex, 50-110 g/m ² duplex
OPTIONS	Paper cassette	Max 3 optional cassettes 500 sheets Paper formats: A5-A4, custom (148 x 210 to 216 x 356 mm) Paper weight: 60-120 g/m ²	IC Card Reader	
	Memory	512 MB memory expansion	IC Card Reader Holder	
			Copy desk	

Product performances are referred to an appropriate use under optimal conditions. With the right to change technical specifications. The registered trademarks are the property of their respective owners. d-Copia 403en and d-Copia 404en are distributed by Olivetti S.p.A. (12/11) - Code: 28563-00